



中国重汽
SINOTRUK

A7(G Series) Mixer

Configuration 6X4



SINO TRUCK COMMERCIAL VEHICLES (M) SDN BHD

Sendok Group Building, Lot 1564, Batu 4, JalanKapar, 42100 Klang, Selangor DarulEhsan, Malaysia.

Tel: +603-3345 5600 Fax: +603-32919658 Email: sendok@po.jaring.my

Website: www.sendokgroup.com



Sendok Group

Model		A7(G Series) 6x4 Mixer					
ENGINE	Model	WD615.47					
	Emission Standard	EURO II					
	Displacement	9.726L					
	Max Output	371HP, 273kW/ 2200rpm according to DIN					
	Max Torque	1500NM at 1100-1600 rpm					
TRANSMISSION	Model	HW19709XST (9F,1R), synchronizer gearbox					
	Ratio	C	1	2	3	4	5
		15.28	12.47	8.79	6.17	4.375	2.85
		6	7	8		R1	
2.01	1.41	1		14.06			
CLUTCH	Type	Dry-diaphragm clutch, driven disc outer diameter 430mm, hydraulically control with air assistance					
FRONT AXLE	Type	VGD95 DRUM, Steering axle with double T- section beam					
REAR AXLE	Type	HC16, casted axle housing, central reduction with planetary wheel reduction. Ratio: 4.42					
SUSPENSION	Front	9 leaf spring					
	Rear	12 leaf spring					
CHASSIS	Frame	Type: Front wide and rear narrow trapezoidal frame Main beam section: Groove 300x80x8mm; Secondary beam section: Groove 282x70x8mm Frame assembly width: Front940mm, rear 850mm					
	Fuel Tank	400L fuel tank with locking fuel cap					
STEERING	Type	Bosch8098, Hydraulic steering with power assistance					
	Ratio	22.2 - 26.2					
BRAKES	Driving Brake	Dual circuit compressed air brake					
	Parking Brake	Spring energy, compressed air operating on rear wheel					
	Auxiliary Brake	Engine exhaust brake					
WHEELS & TIRES	Rim	9.00-22.5, 10 hole-steel					
	Tires	295/80R22.5					
DIMENSION	Wheel Base (mm)	4000 + 1350					
	Overall Dimension (mm)	8513x2496x3850					
	Front Wheel Track (mm)	2050					
	Rear Wheel Track (mm)	1850					
	Front Overhang (mm)	1500					
	Rear Overhang (mm)	2338					
	Approach angle (°)	26					
	Departure angle (°)	48					
	Drum Capacity (m ³)	10					
	Hydraulic Motor	PMP					
	Hydraulic Oil Pump	PMP					
Redection Gears	PMP						
WEIGHT	Curb Weight without Drum (kg)	8750					
	Gross Vehicle weight (kg)	25000 (Peninsular)/ 21000 (Sabah & Sarawak)					
	Front Axle Loading Capacity (kg)	9500					
	Rear Axle Loading Capacity (kg)	16000 x 2					
PERFORMANCE	Max Driving Speed (km/h)	90					
	Max Grade Ability (%)	30					
	Min Turning Circle (m)	22					
	Min Ground Clearance (mm)	260					
ELECTRICS	Operating voltage: 24V, Negative grounded; Starter: 24V, 7.4kW						
	Alternator: 28V, 1540W; Batteries: 2x12, 165Ah						
	Cigar-lighter, horn, headlamp, fog light, brake lights, indicators and reverse lamp						
FUEL CONSUMPTION (L/100km)		31					

Remark: The Company reserves the right to change these terms and conditions at any time without prior notice