



中国重汽
SINOTRUK

SITRAK C9 4x2 & 6x2 (AMT) Euro V



SINO TRUCK COMMERCIAL VEHICLES (M) SDN BHD

Sendok Group Building, Lot 1564, Batu 4, JalanKapar, 42100 Klang, Selangor DarulEhsan, Malaysia.

Tel: +603-3345 5600 Fax: +603-32919658 Email: sendok@po.jaring.my

Website: www.sendokgroup.com



Sendok Group

Model	Sitrak C9	4x2			6x2		
ENGINE	Model	MC11.44-50					
	Emission Standard	EURO V					
	Displacement	10.518L					
	Max Output	440HP , 324kW/ 1900RPM					
	Max Torque	2100NM at 1000-1400 rpm					
	Type	6 cylinder in line, 4 stroke, water cooled, turbo charged & intercooled					
TRANSMISSION	Model	AMT , HW25716XACL, 16 Forward and 2 Reverse					
	Ratio	1	2	3	4	5	6
		12.96	10.8	9	7.5	6.21	5.175
		7	8	9	10	11	12
		4.32	3.6	3	2.5	2.08	1.74
		13	14	15	16	R1	R2
1.44		1.2	1	0.83	11.52	9.6	
FRONT AXLE	Type	Steering axle with T-section beam, Disc Brake.					
REAR AXLE	Type	Disc brake, Single Reduction					
	Ratio	3.7					
SUSPENSION	Front	3 Leaf Spring			3 Leaf Spring		
	Rear	4 Air Balloon Suspension			9 Air Balloon Suspension		
CLUTCH	Model	430 Diaphragm spring					
	Type	Dry single plate, Hydraulic Control with Air Booster					
STEERING	Type	Hydraulic Steering with Power Assistance					
CHASSIS	Frame	High Tesile Steel, Single Layer.					
	Fuel Tank	600L with Locking Fuel Cap			500L with Locking Fuel Cap		
	Fifth Wheel	50# (2"), Optional: 90# (3.5")					
BRAKING SYSTEM	Service Brake	Dual Circuit Compressed Air Brake					
	Parking Brake	Spring Energy, Compressed Air Operating on Rear Wheel					
	Auxiliary Brake	Engine Exhaust Valve Brake					
WHEEL & TYPES	Rim	9.00-22.5, 10 Hole Steel					
	Tyres	295/80R22.5 (Optional: 315/80R22.5)					
DIMENSION	Wheel Base (mm)	3600			3200+1400		
	Front Wheel Track (mm)	2040			2022		
	Rear Wheel Track (mm)	1830					
	Approach Angle (°)	15					
	Departure angle (°)	31					
	Front Overhang (mm)	1500			1500		
	Rear Overhang (mm)	1025			750		
	Overall Dimension (mm)	6100 x 2500 x 3737			6825 x 2500 x 3737		
WEIGHT	Curb Weight (kg)	6800			8500		
	Gross Combination Weight (kg)	40000			50000		
WEIGHT	Front Axle Loading Capacity (kg)	7100					
	Rear Axle Loading Capacity (kg)	13000			13000/ 7000		
PERFORMANCE	Max Driving Speed (km/h)	100					
	Max Gradeability (%)	34					
	Min Ground Clearance (mm)	277					
	Min Turning Diameter (m)	15			15		
ELECTRICS	Operating voltage: 24V, Negative grounded; Starter: 24V, 5.4kW						
	Alternator: 3 Phase, 28V, 1540W; Batteries: 2x12, 165Ah						
	SINOTRUK CAN bus system with VDO numerical control instrument						
DRIVER'S CAB	C9H cabin, Single sleeper, 3-point inertia reel seat belt, adjustable air-ride seats, air conditioning, adjustable steering wheel, quality interior light, powered windows and mirror, outside temperature sensor, cruise control, speed limiter, AEB+LDW+ACC						

Remark: The Company reserves the right to change these terms and conditions at any time without prior notice