



中国重汽
SINOTRUK

Prime Mover T7H 4x2 & 6x2 (AMT) Euro V



SINO TRUCK COMMERCIAL VEHICLES (M) SDN BHD

Sendok Group Building, Lot 1564, Batu 4, JalanKapar, 42100 Klang, Selangor DarulEhsan, Malaysia.

Tel: +603-3345 5600 Fax: +603-32919658 Email: sendok@po.jaring.my

Website: www.sendokgroup.com



Sendok Group

Model	Prime Mover T7H	4x2	6x2				
ENGINE	Model	MC11.44-50					
	Emission Standard	EURO V					
	Displacement	10.518L					
	Max Output	440HP , 316kW/ 1900RPM					
	Max Torque	2100NM at 1000-1400 rpm					
TRANSMISSION	Model	AMT , HW25716XACL, 16 Forward and 2 Reverse					
	Ratio	1	2	3	4	5	6
		12.96	10.8	9	7.5	6.21	5.175
		7	8	9	10	11	12
		4.32	3.6	3	2.5	2.08	1.74
		13	14	15	16	R1	R2
1.44	1.2	1	0.83	11.52	9.6		
FRONT AXLE	Type	Disc brake, Loading capacity 7.5 tonne	Drum brake, Loading capacity 7.5 tonne				
REAR AXLE	Type	Disc brake, Loading capacity 13 tonne	Drum brake, Loading capacity 13 tonne				
	Ratio	3.7					
SUSPENSION	Front	4 Leaf Spring	4 Leaf Spring				
	Rear	Air Balloon Suspension	5 Leaf Spring				
CLUTCH	Model	430 Diaphragm spring					
	Type	Hydraulic Operated Gas Booster					
STEERING	Type	Hydraulic Steering with Power Assistance					
CHASSIS	Frame	U-Profile Parallel Ladder					
	Type	Double Layer Chassis: (8+4/300)					
	Fuel Tank	600L with Locking Fuel Cap	500L with Locking Fuel Cap				
	Fifth Wheel	50# (2"), Optional: 90# (3.5")					
BRAKING SYSTEM	Service Brake	Dual Circuit Compressed Air Brake, Trailer Brake, Drum Brake					
	Parking Brake	Spring Energy, Compressed Air Operating on Rear Wheel					
	Auxiliary Brake	Engine Exhaust Brake					
WHEEL & TYPES	Rim	9.00-22.5, 10 Hole Steel					
	Tyres	295/80R22.5 (Optional: 315/80R22.5)					
DIMENSION	Wheel Base (mm)	3600	3225+1365				
	Front Wheel Track (mm)	2040	2022				
	Rear Wheel Track (mm)	1830					
	Approach Angle (°)	15					
	Departure angle (°)	46					
	Front Overhang (mm)	1500	1540				
	Rear Overhang (mm)	1145	820				
Overall Dimension (mm)	6250 x 2500 x 3050	6950 x 2500 x 3230					
WEIGHT	Curb Weight (kg)	6800	8600				
	Gross Combination Weight (kg)	40000	60000				
WEIGHT	Front Axle Loading Capacity (kg)	7500					
	Rear Axle Loading Capacity (kg)	13000	13000x2				
PERFORMANCE	Max Driving Speed (km/h)	90					
	Max Gradeability (%)	34					
	Min Ground Clearance (mm)	260					
	Min Turning Diameter (m)	7	7.5				
ELECTRICS	Operating voltage: 24V, Negative grounded; Starter: 24V, 5.4kW						
	Alternator: 3 Phase, 28V, 1540W; Batteries: 2x12, 165Ah						
	Cigar-lighter, horn, headlamp, fog light, brake lights, indicators and reverse lamp, tachograph						
DRIVER'S CAB	Sleeper Cab, all steel forward control, hydraulically and manually tiltable to the front, 2 arm windscreen wiper with 3 speeds, laminate windscreen, with casted -in radio aerial, adjustable driver's seat, and rigid adjustable co-driver's seat, with stereo radio/ cassette recorder, sun visor and adjustable steering wheel, air horn, single berth with 4-point support, fully floating suspension and shock absorber, air conditioner, seat belt.						

Remark: The Company reserves the right to change these terms and conditions at any time without prior notice